



- Gently undulating surfaces and edges create the timeless, old-world look of of quarried basalt setts
- Designed for the traditional and efficient random runner bond installation pattern, with common stone widths and various lengths
- Joints and surfaces are designed to create a natural look and minimize furniture wobble
- Made of durable concrete with iron oxide pigments which helps prevent fading from extended UV exposure. Meets or exceeds applicable requirements of ASTM C936 and C1782.
- Light vehicular applications

The Adirondack series features rough shapes, undulating surfaces, and rumpled edges which recall the timeless appeal of quarried basalt setts. Designed for random runner patterns, Adirondack pavers install quickly and creates the aesthetic of historical Old World pavements. A Jumper is also available to break bond lines and expand scale. Adirondack is suitable for Rumbling, which weathers the paver stones by breaking and softening edges and corners.

C


D

## STONE(S)



			_	_	_
Height	in	2.36	2.36	2.36	2.36
	mm	60	60	60	60
Length	in	4.69	6.69	7.81	9.37
	mm	119	170	198.3	238
Width	in	5.51	5.51	5.51	5.51
	mm	140	140	140	140
Units	/pl	100	70	120	100

## **PALLET LAYOUT**



## **NOTES**

Weights are approximate and do not include shipping pallet.

## **PALLET SPECS**

Pallet Weight	2940 lbs		
Sq Ft/Pallet	105 sq.ft.		